

Router Cable/ DSL 4-Port TP-Link TL-R460

- 4 10/100Mbps Auto-Negotiation LAN ports, supporting Auto-MDI/MDIX, 1 10/100Mbps Auto-Negotiation WAN RJ45 port
- Built-in firewall supporting IP address filtering, Domain Name filtering, and MAC address filtering
- Supports access control based on time of day, parents and network administrators can establish restricted access policies for children or staffs
- Supports firmware upgrade, Remote and Web management
- Complies with IEEE 802.3, IEEE 802.3u standards
- 1 10/100Mbps Auto-Negotiation WAN RJ45 port, 4 10/100Mbps Auto-Negotiation LAN ports, supporting Auto-MDI/MDIX
- Shares data and Internet access for users, supporting PPPoE, Dynamic IP, Static IP, L2TP, BigPond Cable Internet access
- Connecting Internet on demand and disconnecting when idle for PPPoE
- Supports TCP/IP, PPPoE, DHCP, ICMP, NAT
- Built-in NAT and DHCP server supporting static IP address distributing
- Built-in firewall supporting IP address filtering, Domain Name filtering, and MAC address filtering
- Supports Virtual Server, Special Application, and DMZ host
- Supports UPnP, Dynamic DNS, Static Routing, Flow Statistics, VPN pass-through
- Supports connecting/disconnecting Internet on a specified time of day
- Supports access control based on time of day, parents and network administrators can establish restricted access policies for children or staffs
- Provides 802.1x authentication for WAN port
- Supports ICMP-FLOOD, UDP-FLOOD, TCP-SYN-FLOOD filter
- Ignores Ping packets from WAN or LAN ports
- Supports firmware upgrade, Remote and Web management

Standard and Protocol		IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.1X, TCP/IP, DHCP, ICMP, NAT, PPPoE, SNTP
Port		LAN 4 10/100M Auto-Negotiation RJ45 ports (Auto MDI/MDIX)
		WAN 1 10/100M Auto-Negotiation RJ45 port (Auto MDI/MDIX)
Network Media		10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
LED Indicators	LAN/WAN	Link/Act, 100Mbps
	Else	M1, M2
Power and Consumption		Input: 9V~50Hz 0.8A Consumption: 3.6W(Max)
Safety & Emission		FCC, CE
Dimensions (L x W x H)		7.3 x 5.7 x 1.7 in.(186 x 146 x 44 mm)
Operating environment		Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing



HOT TOOLS . COOL PRICE